



## Advantages of ASI Tape Detector For 205 H<sub>2</sub>S in Liquids Analyzers

- ✓ **Specific only to H<sub>2</sub>S** No known cross-interferences proven by thousands of world wide applications
- ✓ **No calibrations required** Based on exclusive ASI Membrane Technologies and advanced Tape detector
- ✓ **Conformity to ASTM analytical methods** D4084-82, D4468-85, and D4045-81
- ✓ **Automatic self-zero** The ASI H<sub>2</sub>S analyzer does not suffer from a 'zero drift' as seen in other analyzers thus eliminating zero gas requirements
- ✓ **Versatile** The analyzer will not suffer in the event of process changes no matter how drastic
- ✓ **Wide Range Ability** The analyzer is capable of measuring from the PPB levels through PPM up to saturation
- ✓ **Hassle free** ASI advanced Tape detector only needs 2 to 4 tape changes per year (typical) on standard 100 foot tape roll
- ✓ **Linear Response** The analyzer is innately linear in response, no need to calibrate in the field
- ✓ **Field-proven technology** The 205 analyzer is field-proven by installations all over the world and trusted by major oil & gas companies worldwide including Preferred Vendor status

(281) 516-3950 FAX (281) 351-8925

[Sales@asikeco.com](mailto:Sales@asikeco.com) or [Service@asikeco.com](mailto:Service@asikeco.com)

[www.asikeco.com](http://www.asikeco.com)